



SPECIFICATIONS





Shower Only Trim Kit - 11 Series

Shower Kit with 6" Arm and Flange, Eight function Shower & Valve Trim – Requires M410 Rough-in Valve

Shower Head - MLR8FSHD

- 1/2" -14 NPSM Connection
- Self Cleaning Rubber Jets
- Eight Function Spray
- Max Flow Rate: 1.75 GPM @ 60 PSI (6.6L/Min)
- 100% Factory Pressure Tested

Shower Arm & Flange – ML6SA & MLRSF

- 6" Shower Arm for Wall Mount Application
- Finished Metal Body
- 2 x ½" -14 NPT Connection
- Metal, 2 ½" Dia Round Shower Flange

Valve Only Trim – JV511

- Includes Ceramic Disc Cartridge
- Requires Mainline M410 Rough-in Valve
- Easy Press to Place Installation
- Deep Installation Adapters (Optional)

JV118

Specified model meets or exceeds the following:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- EPA WaterSense®
- ADA for lever handle control

AVAILABLE FORMATS

Multiple Kit Formats Available Visit mainlinecollection.ca

Mainline products have been manufactured under the highest standards of quality and workmanship. That is why we offer "Limited Lifetime" warranty on the function and finish of our shower faucets.



Standards & Certifications			
245	NSF/ANSI 372		







Please **visit www.mainlinecollection.ca** for available finishes. Finish is defined by additional suffix. Please **visit www.mainlinecollection.ca** for detailed Specification of components.

SUBMITTAL INFORMATION

Name:	Contractor:
Location:	Contact #:
Notes:	