



SPECIFICATIONS





Shower Only Trim Kit - 21RDS Series

Shower Kit with 17 Right Angle" Arm and Flange, Single function Rain Shower, Diverter Tub Spout & Valve Trim – Requires M410 Rough-in Valve

Shower Head - MLRRSH

- 1/2"-14 NPSM Connection
- Self Cleaning Rubber Jets
- Single Function Rain
- Max Flow Rate: 1.75 GPM @ 60 PSI (6.6L/Min)
- 100% Factory Pressure Tested

Valve Only Trim – JV511

- Includes Ceramic Disc Cartridge
- Requires Mainline M410 Rough-in Valve
- Easy Press to Place Installation
- Deep Installation Adapters (Optional)

Shower Arm & Flange - ML17RASA & MLRSF

- 17" Right Angled Shower Arm for Wall Mount Application
- Finished Metal Body
- Wall Side 1/2" -14 NPT Connection
- Shower side ½" 14 NPSM
- Metal, 2 ½" Dia Round Shower Flange

<u>Tub Spout - MLRDSPT</u>

- Diverter Tub Spout
- Die-Cast
- 1/2"-14NPT/SLIPFIT
- · CUPC Certified

JV21RDS

Specified model meets or exceeds the following:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- EPA WaterSense®
- ADA for lever handle control

AVAILABLE FORMATS

Multiple Kit Formats Available Visit mainlinecollection.ca

Mainline products have been manufactured under the highest standards of quality and workmanship. That is why we offer "Limited Lifetime" warranty on the function and finish of our shower faucets.



Standards & Certifications NSF/ANSI 372 A NSF/ANSI 372







Available Finishes			
/	/		/

Please **visit www.mainlinecollection.ca** for available finishes. Finish is defined by additional suffix. Please **visit www.mainlinecollection.ca** for detailed Specification of components.

SUBMITTAL INFORMATION

Name:	Contractor:
Location:	Contact #:
Notes:	